



Link-Seal tætninger.
Tætning af EPDM.
Trykplade af armeret plast.
Bolte af AISI 316.
Vatech nr. 101700.xxx



Type	Pris pr. led kr.
LS-200-A4	33,00
LS-275-A4	41,00
LS-300-A4	61,00
LS-315-A4	99,00
LS-325-A4	99,00
LS-340-A4	96,00
LS-360-A4	121,00
LS-400-A4	161,00
LS-410-A4	148,00
LS-425-A4	161,00
LS-475-A4	161,00
LS-500-A4	321,00
LS-525-A4	321,00
LS-575-A4	321,00
LS-600-A4	1.032,00

Link-Seal tætninger.
Tætning af NBR.
Trykplade af armeret plast.
Bolte af AISI 316.
Vatech nr. 101701.xxx



Type	Pris pr. led kr.
LS-200-A4	38,00
LS-275-A4	47,50
LS-300-A4	74,00
LS-315-A4	108,00
LS-325-A4	94,00
LS-340-A4	85,00
LS-360-A4	109,00
LS-400-A4	150,00
LS-410-A4	120,00
LS-425-A4	150,00
LS-475-A4	150,00
LS-500-A4	307,00
LS-525-A4	307,00
LS-575-A4	307,00
LS-600-A4	1.097,00

Tabel
Dimensionstabel for Link-Seal tætninger til stålør uden coating. Efter DIN 2448 og 2458.

Rør Ø	Diamantboret Hul Ø	Antal led	Type
17,2	50-54	4	LS-275
21,3	54-60	5	LS-275
26,9	59-61	5	LS-275
33,7	67-70	6	LS-275
42,4	75-77	7	LS-275
48,3	86-91	5	LS-300
60,3	94-98	10	LS-275
76,1	115-120	8	LS-300
88,9	127-130	9	LS-300
101,6	145-150	10	LS-315
108,0	152-158	11	LS-315
114,3	158-164	11	LS-315
133,0	202-214	10	LS-360
139,7	207-220	10	LS-360
159,0	225-240	11	LS-360
168,3	242-255	7	LS-400

Tabel
Dimensionstabel for Link-Seal tætninger til stålør uden coating. Efter DIN 2448 og 2458.

Rør Ø	Diamantboret Hul Ø	Antal led	Type
219,1	294-305	9	LS-400
273,0	358-367	15	LS-475
323,9	398-412	12	LS-400
355,6	439-448	18	LS-475
406,4	481-495	15	LS-400
457,0	530-545	17	LS-400
508,0	620-632	18	LS-525
559,0	680-700	20	LS-500
610,0	693-704	30	LS-475
660,0	773-783	23	LS-525
711,2	825-835	24	LS-525
762,0	875-885	26	LS-525
812,8	936-950	28	LS-500
914,4	1030-1037	31	LS-525
1016,0	1130-1140	34	LS-525

Tabel
Dimensionstabel for Link-Seal tætninger til rustfrie stålør.

Rør Ø	Diamantboret hul Ø	Antal led	Type
17	50-54	4	LS-275
20	53-58	5	LS-275
22	55-60	5	LS-275
35	69-74	7	LS-275
44	77-82	8	LS-275
54	87-93	9	LS-275
69	106-113	7	LS-300
84	122-127	8	LS-300
104	141-148	10	LS-300
114	166-180	11	LS-340
129	166-173	12	LS-300
139	190-198	7	LS-325
154	202-212	7	LS-325
168	245-255	7	LS-400

Tabel
Dimensionstabel for Link-Seal tætninger til rustfrie stålør.

Rør Ø	Diamantboret hul Ø	Antal led	Type
204	254-263	9	LS-325
219	267-275	10	LS-325
254	328-340	10	LS-400
273	350-363	11	LS-400
304	380-392	12	LS-400
323	397-412	12	LS-400
355	414-427	13	LS-425
406	480-495	15	LS-400
506	580-590	18	LS-400
606	680-693	22	LS-400
708	785-795	25	LS-400
808	885-895	29	LS-400
910	970-980	32	LS-425
1010	1085-1095	35	LS-400

Tabel
Dimensionstabel for Link-Seal tætninger til PP- PE- og PVC-rør. (PE-rør ≤ Ø 400 skal være PE-100 og PN 10).

Rør Ø	Diamantboret hul Ø	Antal led	Type
16	48-55	4	LS-275
20	52-59	5	LS-275
25	57-62	5	LS-275
32	64-71	6	LS-275
40	73-79	7	LS-275
50	93-102	6	LS-315
63	95-102	10	LS-275
75	118-127	8	LS-315
90	126-134	9	LS-300
110	146-154	10	LS-300
125	168-176	12	LS-315
140	179-183	13	LS-300
160	197-203	14	LS-300
180	238-250	7	LS-425
200	249-258	9	LS-325
225	274-283	10	LS-325

Tabel
Dimensionstabel for Link-Seal tætninger til PP- PE- og PVC-rør. (PE-rør ≤ Ø 400 skal være i PE-100 og PN 10).

Rør Ø	Diamantboret hul Ø	Antal led	Type
250	298-307	11	LS-325
280	328-337	12	LS-325
315	368-373	14	LS-325
355	405-412	15	LS-325
400	450-457	17	LS-325
450	530-540	17	LS-400
500	575-585	18	LS-400
560	637-650	20	LS-400
630	705-718	23	LS-400
670	745-757	24	LS-400
710	785-795	25	LS-400
800	875-885	28	LS-400
900	975-985	32	LS-400
1000	1075-1085	35	LS-400
1200	1275- 285	42	LS-400